



CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

Tel: +86-755- 27521059 Fax: +86-755- 27521011 Http://www.sz-ctc.org.cn

TEST REPORT

Report No.: **CTC20210068E01**

Applicant: **XonTel Technology Trd. Co. W.L.L**

Address.....: Kuwait City, Qibla, Aladel Tower, F21, state of Kuwait

Manufacturer.....: XonTel Technology Trd. Co. W.L.L

Address.....: Kuwait City, Qibla, Aladel Tower, F21, state of Kuwait

Product Name: **IP Phone**

Trade Mark: XonTel

Model/Type reference.....: XT-40G

Listed Model(s): N/A

Standard: **EN 55032: 2015/AC: 2016**
EN 55035: 2017
EN 61000-3-2: 2014
EN 61000-3-3: 2013
EN 55024: 2010+A1: 2015

Date of receipt of test sample...: Mar. 10, 2020

Date of testing.....: Mar. 11, 2020 to Mar. 23, 2020

Date of issue.....: Jan. 20, 2021

Result.....: **PASS**

Compiled by:

(Printed name+signature)

Terry Su

Terry Su

Supervised by:

(Printed name+signature)

Miller Ma

Miller Ma

Approved by:

(Printed name+signature)

Walter Chen

Walter Chen

Testing Laboratory Name: **CTC Laboratories, Inc.**

Address.....: 2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CTC. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CTC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.



Table of Contents

Page

1. TEST SUMMARY	3
1.1. TEST STANDARDS.....	3
1.2. REPORT VERSION.....	3
1.3. TEST DESCRIPTION.....	4
1.4. TEST FACILITY	5
1.5. MEASUREMENT UNCERTAINTY	5
1.6. ENVIRONMENTAL CONDITIONS	6
2. GENERAL INFORMATION	7
2.1. CLIENT INFORMATION	7
2.2. GENERAL DESCRIPTION OF EUT	7
2.3. ACCESSORY EQUIPMENT INFORMATION	8
2.4. DESCRIPTION OF TEST MODES	9
2.5. MEASUREMENT INSTRUMENTS LIST	10
3. EMC EMISSION TEST.....	12
3.1. RADIATED EMISSION	12
3.2. CONDUCTED EMISSION (AC MAINS).....	22
3.3. CONDUCTED EMISSION (SIGNAL MAINS)	25
3.4. HARMONIC CURRENT EMISSION.....	28
3.5. VOLTAGE FLUCTUATION AND FLICKER.....	30
4. EMS IMMUNITY TEST	32
4.1. ELECTROSTATIC DISCHARGE	33
4.2. RADIO FREQUENCY ELECTROMAGNETIC FIELD	36
4.3. FAST TRANSIENTS COMMON MODE	37
4.4. SURGE	38
4.5. RADIO FREQUENCY COMMON MODE	39
4.6. VOLTAGE DIPS AND INTERRUPTIONS.....	40
5. EUT TEST PHOTOS.....	41
6. PHOTOGRAPHS OF EUT CONSTRUCTIONAL	47



1. TEST SUMMARY

1.1. Test Standards

The tests were performed according to following standards:

[EN 55032: 2015/AC: 2016](#)—Electromagnetic compatibility of multimedia equipment—Emission Requirements

[EN 55035:2017](#)—Electromagnetic compatibility of multimedia equipment—Immunity requirements

[EN 61000-3-2: 2014](#)—Electromagnetic compatibility (EMC) - Part 3-2: Limits - Limits for harmonic current emissions (equipment input current ≤ 16 A per phase)

[EN 61000-3-3: 2013](#)—Electromagnetic compatibility (EMC) - Part 3-3: Limits - Limitation of voltage changes, voltage fluctuations and flicker in public low-voltage supply systems, for equipment with rated current ≤ 16 A per phase and not subject to conditional connection

[EN 55024: 2010+A1: 2015](#)—Information technology equipment — Immunity characteristics — Limits and methods of measurement

1.2. Report version

Revised No.	Date of issue	Description
01	Jan. 20, 2021	Original

Note: Update applicant, manufacturer, trademark and model name, This report is based on the report of CTC20200268E02.



1.3. Test Description

Emission			
Test Item	Standard requirement	Result	Test Engineer
Radiated Emission	EN 55032: 2015/AC: 2016	Pass	Terry Su
Conducted Emission (AC Mains)	EN 55032: 2015/AC: 2016	Pass	Jon Huang
Conducted Emission (Signal Mains)	EN 55032: 2015/AC: 2016	Pass	Jon Huang
Harmonic Current Emissions	EN61000-3-2: 2014	N/A	N/A
Voltage Fluctuations and Flicker	EN61000-3-3: 2013	Pass	Lance Lan
Immunity			
Test Item	Standard requirement (EN 55024: 2010+A1: 2015/ EN55035: 2017)	Result	Test Engineer
Electrostatic Discharge	EN 61000-4-2: 2009	Pass	Lance Lan
Radio Frequency Electromagnetic Field	EN 61000-4-3: 2006/A2: 2010	Pass	Lance Lan
Electrical Fast Transient / Burst	EN 61000-4-4: 2012	Pass	Lance Lan
Surges	EN 61000-4-5: 2014/A1: 2017	Pass	Lance Lan
Injected Current	EN 61000-4-6: 2014/AC:2015	Pass	Lance Lan
Voltage Dips and Interruptions	EN 61000-4-11: 2004/A1:2017	Pass	Lance Lan

Note: "N/A" is applicable.

The measurement uncertainty is not included in the test result.



1.4. Test Facility

CTC Laboratories, Inc.

Add: 2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L5365

CTC Laboratories, Inc. has been assessed and proved to be in compliance with CNAS-CL01 Accreditation .Criteria for Testing and Calibration Laboratories (identical to ISO/IEC17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories.

A2LA-Lab Cert. No.: 4340.01

CTC Laboratories, Inc. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

Industry Canada (Registration No.: 9783A, CAB Identifier: CN0029)

CTC Laboratories, Inc. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Jan, 2016.

FCC (Registration No.: 951311, Designation Number CN1208)

CTC Laboratories, Inc. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 951311, Aug 26, 2017.

1.5. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the CTC Laboratories, Inc. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Below is the best measurement capability for CTC Laboratories, Inc.



A. Conducted Measurement:

Test Site	Method	Measurement Frequency Range	U · (dB)	NOTE
C01	ANSI	150 KHz ~ 30MHz	3.2	/

B. Radiated Measurement:

Test	Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	3.5 dB	(1)
Radiated Emission	1~18GHz	5.1 dB	(1)

Note: (1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

1.6. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	22°C ~ 27°C
Relative Humidity	51 % ~ 65 %
Air Pressure	101kPa



2. GENERAL INFORMATION

2.1. Client Information

Applicant:	XonTel Technology Trd. Co. W.L.L
Address:	Kuwait City, Qibla, Aladel Tower, F21, state of Kuwait
Manufacturer:	XonTel Technology Trd. Co. W.L.L
Address:	Kuwait City, Qibla, Aladel Tower, F21, state of Kuwait

2.2. General Description of EUT

Product Name:	IP Phone
Trade Mark:	XonTel
Model/Type reference:	XT-40G
Listed Model(s):	N/A
Power supply:	5Vdc/2A from AC/DC Adapter Supplied from POE
Adapter 1 Model:	F12W8-050200SPAV Input: AC100-240V 50/60Hz 0.3A Output:5V/2A
Adapter 2 Model:	F12W8-050200SPAB Input: AC100-240V 50/60Hz 0.3A Output:5V/2A
Hardware version:	N/A
Software version:	N/A



2.3. Accessory Equipment information

Equipment Information			
Name	Model	S/N	Manufacturer
IP Phone	X7	JGB28B000005	Fanvil
POE Supply	H3C S1208-PWR	219801A0SYM17B0000LS	H3C
Router	FAST 5280	253703944	Sagemcom
Headset	---	X18033620	Fanvil
Cable Information			
Name	Shielded Type	Ferrite Core	Length
Lan Cable	N/A	N/A	1M



2.4. Description of Test Modes

Test mode	Communicate by hands free	Communicate by telephone receiver	AC/DC Adapter	POE Supply
1	■		■	
2		■	■	
3	■			■
4		■		■

Note: ■ is operation mode.

Pre-scan above all test mode, found below test mode which it was worse case mode, so only show the test data for worse case mode on the test report.

Test item	Test mode
Radiated Emission	1, 4
Conducted Emission(AC Mains)	2
Conducted Emission(Signal Mains)	2, 4
Harmonic Current Emissions	N/A
Voltage Fluctuations and Flicker	1
Radio Frequency Electromagnetic Field	All
Electrostatic Discharge	All
Electrical Fast Transient / Burst	All
Injected Current	All
Voltage Dips and Interruptions	1, 2
Surges	All

Note: "N/A" is applicable.



2.5. Measurement Instruments List

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	LISN	R&S	ENV216	101112	Dec. 27, 2020
2	LISN	R&S	ENV216	101113	Dec. 27, 2020
3	ISN CAT5	Schwarzbeck	NTFM8158	CAT5-8158-0046	Dec. 27, 2020
4	ISN CAT6	Schwarzbeck	NTFM8158	CAT6-8158-0046	Dec. 27, 2020
5	EMI Test Receiver	R&S	ESCI	100658	Dec. 27, 2020
6	Current Probe	CYBERTEK	EM5011	E165011025	Dec. 27, 2020

Radiated Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-1013	Dec. 27, 2020
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-647	Dec. 27, 2020
3	Spectrum Analyzer	R&S	FSU26	100105	Dec. 27, 2020
4	Spectrum Analyzer	R&S	FSV40-N	101331	Dec. 27, 2020
5	Pre-Amplifier	SONOMA	310	186194	Dec. 27, 2020
6	Low Noise Pre-Amplifier	EMCI	EMC051835	980075	Dec. 27, 2020
7	Test Receiver	R&S	ESCI7	100967	Dec. 27, 2020
8	Antenna Mast	UC	UC3000	N/A	N/A
9	Turn Table	UC	UC3000	N/A	N/A

Harmonic Current Emissions & Voltage Fluctuations and Flicker					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Harmonic Flicker Analyzer	Voltech	PM6000	200006700723	Dec. 27, 2020
2	Programmable AC Power Source	Mtoni	PHF1530	MTPS001	Dec. 27, 2020

Electrostatic Discharge					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	ESD Simulator	EM TEST	DITO	V1113109156	Dec. 27, 2020

RF Electromagnetic Field					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	High Gain Log-Periodic Antenna	R&S	HL046E	100037	Dec. 27, 2020
2	Stacked Log.-Per. Antenna	Schwarzbeck	STLP 9149	9149-658	Dec. 27, 2020
3	Power Amplifier	BONN ELEKTRONIK	BLWA0830-160/100/40D	76788	Dec. 27, 2020
4	Power Amplifier	Micotop	MPA-3-6G-50	MPA1706258	Dec. 27, 2020
5	PSG Analog Signal Generator	Agilent	E8257D	MY46521908	Dec. 27, 2020
6	Turn Table	UC	UC3000	N/A	N/A



Fast Transients Common Mode					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Electrical fast transient generator	3ctest	EFT-4003G	EC0471140	Dec. 27, 2020
2	Coupling/Decoupling Clamp	3ctest	EFTC	EC0441141	Dec. 27, 2020

Surges					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Surge generator	3ctest	SG-5006G	EC5581149	Dec. 27, 2020
2	Surge CDN	3ctest	SGN-20G	EC5551128	Dec. 27, 2020
3	Network Surge Generator	3ctest	CWS 600T	ES0311603	Dec. 27, 2020
4	Network Surge CDN	3ctest	CDN 405T8AI	ES2731605	Dec. 27, 2020

RF Common Mode					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	C/S Generator	SCHLODER	CDG6000	126A1266	Dec. 27, 2020
2	Coupling/Decoupling Network	SCHLODER	CDN M2+3	A2210258	Dec. 27, 2020
3	Coupling/Decoupling Network	TESEQ GmbH	CDN T8-10	45011	Dec. 27, 2020
4	6dB Attenuator	N/A	100W/6dB	N/A	Dec. 27, 2020

Voltage dips and interruptions					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Voltage dips and up generator	3ctest	VDG-1105G	EC0171116	Dec. 27, 2020

Note: The Cal. Interval was one year.

3. EMC EMISSION TEST

3.1. Radiated Emission

LIMIT


Please refer to CENELEC EN 55032 Annex A Table A.4 & A.5

Frequency range (MHz)	Quasi-peak limits dB μ V/m@3m	Quasi-peak limits dB μ V/m@10m
30~230	40	30
230~1000	47	37


Frequency range (GHz)	Average limits dB μ V/m@3m	Peak limits dB μ V/m@3m
1 ~ 3	50	70
3 ~ 6	54	74

TEST CONFIGURATION

(A) Radiated Emission Test Set-Up Frequency below 1 GHz



(B) Radiated Emission Test Set-Up Frequency above 1GHz



TEST PROCEDURE

Please refer to CENELEC EN 55032 Clause 6.3 for the measurement methods


TEST MODE


Please refer to the Clause 2.4

TEST RESULTS




(1) Below 1G







Test Mode	6
Polarization	Horizontal



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector
1	37.2855	-17.68	38.25	20.57	40.00	-19.43	QP
2	56.7917	-18.28	41.46	23.18	40.00	-16.82	QP
3	187.0958	-19.87	45.98	26.11	40.00	-13.89	QP
4	256.5211	-18.96	49.20	30.24	47.00	-16.76	QP
5	350.4768	-16.71	49.95	33.24	47.00	-13.76	QP
6	986.0717	-6.97	39.97	33.00	47.00	-14.00	QP

Remark:


1. Factor (dB/m) = Antenna Factor (dB/m) + Cable Factor (dB) - Pre-amplifier Factor


2. Margin value = Level - Limit value







(2) Above 1G









3.2. Conducted Emission (AC Mains)

LIMIT


Please refer to CENELEC EN 55032 Annex A3 Table A.10

Frequency range MHz	Limits dB(μ V)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

NOTE 1 The lower limit shall apply at the transition frequencies.

NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.

TEST CONFIGURATION



Note: 1.Support units were connected to second LISH.
2.Both of LISHs (AMN) are 80 cm from EUT and at least 80
from other units and other metal planes

TEST PROCEDURE

Please refer to CENELEC EN 55032 Annex A3 Table A.8


TEST MODE

Please refer to the Clause 2.4

TEST RESULTS



Test Mode	2
Polarization	L



Final Measurement Detector 1


Frequency (MHz)	QuasiPeak (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.218300	36.3	1000.00	9.000	On	L1	9.4	26.6	62.9	
0.519130	32.6	1000.00	9.000	On	L1	9.4	23.4	56.0	
0.538120	34.0	1000.00	9.000	On	L1	9.4	22.0	56.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.519130	26.6	1000.00	9.000	On	L1	9.4	19.4	46.0	
0.538120	28.2	1000.00	9.000	On	L1	9.4	17.8	46.0	
0.956170	21.2	1000.00	9.000	On	L1	9.5	24.8	46.0	



Test Mode	2
Polarization	N



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.157990	38.6	1000.00	9.000	On	N	9.4	27.0	65.6	
0.515000	32.5	1000.00	9.000	On	N	9.4	23.5	56.0	
0.533840	34.5	1000.00	9.000	On	N	9.4	21.5	56.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.519130	29.3	1000.00	9.000	On	N	9.4	16.7	46.0	
0.531710	30.8	1000.00	9.000	On	N	9.4	15.2	46.0	
0.941020	23.3	1000.00	9.000	On	N	9.5	22.7	46.0	

3.3. Conducted Emission (Signal Mains)


LIMIT

Please refer to CENELEC EN 55032 Annex A Table A.12

Frequency range (MHz)	Voltage Limits dB(μ V)		Current limits dB(μ A)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	84 ~ 74	74 ~ 64	40 ~ 30	30 ~ 20
0.5 ~ 30	74	64	30	20

Note: if “150 Ω to 50 Ω adaptor” applied, correction factor of 9.5dB should be added to the test data.

TEST CONFIGURATION



TEST PROCEDURE

Please refer to CENELEC EN 55032 section C4


TEST MODE

Please refer to the Clause 2.4

TEST RESULTS



Test Mode	2
Polarization	Lan Port



Final Measurement Detector 1


Frequency (MHz)	QuasiPeak (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.519130	48.9	1000.00	9.000	On	L1	9.4	25.1	74.0	
0.540270	50.7	1000.00	9.000	On	L1	9.4	23.4	74.0	
4.972300	42.1	1000.00	9.000	On	L1	9.5	32.0	74.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
0.519130	44.9	1000.00	9.000	On	L1	9.4	19.1	64.0	
0.535980	47.3	1000.00	9.000	On	L1	9.4	16.7	64.0	
3.309170	39.9	1000.00	9.000	On	L1	9.5	24.1	64.0	



Test Mode	4
Polarization	Lan Port



Final Measurement Detector 1

Frequency (MHz)	QuasiPeak (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
2.338220	53.2	1000.00	9.000	On	N	9.5	20.8	74.0	
3.335700	55.0	1000.00	9.000	On	N	9.5	19.0	74.0	
3.671090	53.5	1000.00	9.000	On	N	9.5	20.5	74.0	

Final Measurement Detector 2

Frequency (MHz)	Average (dBμ V)	Meas. Time (ms)	Bandwidth (kHz)	Filter	Line	Corr. (dB)	Margin (dB)	Limit (dBμ V)	Comment
2.338220	53.2	1000.00	9.000	On	N	9.5	10.8	64.0	
3.335700	55.2	1000.00	9.000	On	N	9.5	8.8	64.0	
3.671090	53.8	1000.00	9.000	On	N	9.5	10.2	64.0	



3.4. Harmonic Current Emission

LIMIT

EN61000-3-2 Clause 7

➤ Class A equipment

Harmonic order n	Maximum permissible harmonic current A
Odd harmonics	
3	2,30
5	1,14
7	0,77
9	0,40
11	0,33
13	0,21
$15 \leq n \leq 39$	$0,15 \frac{15}{n}$
Even harmonics	
2	1,08
4	0,43
6	0,30
$8 \leq n \leq 40$	$0,23 \frac{8}{n}$

➤ Class B equipment

not exceed the values given in Class A limit multiplied by a factor of 1,5

➤ Class C equipment

Active input power >25 W

Harmonic order n	Maximum permissible harmonic current expressed as a percentage of the input current at the fundamental frequency %
2	2
3	$30 \cdot \lambda^*$
5	10
7	7
9	5
$11 \leq n \leq 39$ (odd harmonics only)	3
* λ is the circuit power factor	

Active input power ≤ 25 W

Harmonic order n	Maximum permissible harmonic current per watt mA/W	Maximum permissible harmonic current A
3	3,4	2,30
5	1,9	1,14
7	1,0	0,77
9	0,5	0,40
11	0,35	0,33
$13 \leq n \leq 39$ (odd harmonics only)	$\frac{3,85}{n}$	See Table 1

or the third harmonic current, expressed as a percentage of the fundamental current, shall not exceed 86 % and the fifth harmonic current shall not exceed 61 %. Also, the waveform of the input current shall be such that it reaches the 5 % current threshold before or at 60°, has its peak value before or at 65° and does not fall below the 5 % current threshold before 90°, referenced to any zero crossing of the fundamental supply voltage. The current threshold is 5 % of the highest

CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and

Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>




absolute peak value that occurs in the measurement window, and the phase angle measurements are made on the cycle that includes this absolute peak value

➤ **Class D equipment**

Harmonic order n	Maximum permissible harmonic current per watt mA/W	Maximum permissible harmonic current A
3	3,4	2,30
5	1,9	1,14
7	1,0	0,77
9	0,5	0,40
11	0,35	0,33
$13 \leq n \leq 39$ (odd harmonics only)	$\frac{3,85}{n}$	See Table 1

TEST CONFIGURATION



TEST PROCEDURE

Please refer to EN61000-3-2 for the measurement methods.

TEST MODE

Please refer to the Clause 2.4

TEST RESULTS

Note: The power of the EUT is less than 75W, So this test item is not applicable.


3.5. Voltage Fluctuation and Flicker

LIMIT

Please refer to EN61000-3-3

Tests	Limits		Descriptions
	IEC555-3	IEC/EN 61000-3-3	
Pst	≤ 1.0 , $T_p = 10$ min.	≤ 1.0 , $T_p = 10$ min.	Short Term Flicker Indicator
Plt	N/A	≤ 0.65 , $T_p = 2$ hr.	Long Term Flicker Indicator
dc	$\leq 3\%$	$\leq 3.3\%$	Relative Steady-State V-Chang
dmax	$\leq 4\%$	$\leq 4\%$	Maximum Relative V-change
d (t)	N/A	$\leq 3.3\%$ for > 500 ms	Relative V-change characteristic

TEST CONFIGURATION



TEST PROCEDURE

Please refer to EN61000-3-3 for the measurement methods.

TEST MODE

Please refer to the Clause 2.4

**TEST RESULTS**

Test Mode		1		
Voltech IEC61000-3 Windows Software 1.27.13		Test Date: 18 Mar 2020 10:24		
Type of Test: Flickermeter Test - Table (EN61000-3-3:2013)				
Power Analyzer: Voltech PM6000 SN: 200006700723 Firmware Version: v1.22.07RC6				
Channel(s):				
1. SN: 090015502565, 28 Adjusted Date: 2 AUG 2013. 2. SN: 090015500533, 28 Adjusted Date: 19 MAR 2010.				
3. SN: 090015502345, 28 Adjusted Date: 21 JUN 2012. 4. SN:None Adjusted Date:None				
5. SN:None Adjusted Date:None 6. SN:None Adjusted Date:None				
Shunt(s):				
1. SN: 091024303183, 4 Adjusted Date: 8 AUG 2013. 2. SN: 091024302146, 4 Adjusted Date: 22 JUN 2012.				
3. SN: 091024302144, 4 Adjusted Date: 22 JUN 2012. 4. SN:None Adjusted Date:None				
5. SN:None Adjusted Date:None 6. SN:None Adjusted Date:None				
AC Source: Mains / Manual Source				
Overall Result:		Notes:		
PASS		Measurement method - Voltage		
	Pst	dc (%)	dmax (%)	Tmax(> 3.3%)(ms)
Limit	1.000	3.300	4.000	500
Reading 1	0.359	0.000	0.819	0

4. EMS IMMUNITY TEST

Performance criteria

General performance criteria

- Performance criteria A for immunity tests with phenomena of a continuous nature;
- Performance criteria B for immunity tests with phenomena of a transient nature;
- Performance criteria C for immunity tests with power interruptions exceeding a certain time.

The equipment shall meet the minimum performance criteria as specified in the following.

Criteria	During test	After test
A	Shall operate as intended. May show degradation of performance (see note 1). Shall be no loss of function. Shall be no unintentional transmissions.	Shall operate as intended. Shall be no degradation of performance (see note 2). Shall be no loss of function. Shall be no loss of stored data or user programmable functions.
B	May show loss of function (one or more). May show degradation of performance (see note 1). No unintentional transmissions.	Functions shall be self-recoverable. Shall operate as intended after recovering. Shall be no degradation of performance (see note 2). Shall be no loss of stored data or user programmable functions.
C	May be loss of function (one or more).	Functions shall be recoverable by the operator. Shall operate as intended after recovering. Shall be no degradation of performance (see note 2).

NOTE 1:

Degradation of performance during the test is understood as a degradation to a level not below a minimum performance level specified by the manufacturer for the use of the apparatus as intended. In some cases the specified minimum performance level may be replaced by a permissible degradation of performance.

If the minimum performance level or the permissible performance degradation is not specified by the manufacturer then either of these may be derived from the product description and documentation (including leaflets and advertising) and what the user may reasonably expect from the apparatus if used as intended.

NOTE 2:

No degradation of performance after the test is understood as no degradation below a minimum performance level specified by the manufacturer for the use of the apparatus as intended. In some cases the specified minimum performance level may be replaced by a permissible degradation of performance. After the test no change of actual operating data or user retrievable data is allowed.

If the minimum performance level or the permissible performance degradation is not specified by the manufacturer then either of these may be derived from the product description and documentation (including leaflets and advertising) and what the user may reasonably expect from the apparatus if used as intended.

4.1. Electrostatic Discharge

PERFORMANCE CRITERION


Standard	Criterion
EN 50024/EN 55035/EN 61000-4-2	Criteria B

TEST LEVEL

Contact Discharge at $\pm 2\text{kV}$, $\pm 4\text{kV}$

Air Discharge at $\pm 2\text{kV}$, $\pm 4\text{kV}$, $\pm 8\text{kV}$

TEST CONFIGURATION



TEST PROCEDURE

Please refer to EN 61000-4-2 for the measurement methods.

Contact Discharge:

The ESD generator is held perpendicular to the surface to which the discharge is applied and the tip of the discharge electrode touch the surface of EUT. Then turn the discharge switch. The generator is then re-triggered for a new single discharge and repeated at least 10 times for each pre-selected test point. This procedure shall be repeated until all the air discharge completed.

Air Discharge:

Air discharge is used where contact discharge can't be applied. The round discharge tip of the discharge electrode shall be approached as fast as possible to touch the EUT. After each discharge, the discharge electrode shall be removed from the EUT. The generator is then re-triggered for a new single discharge and repeated at least 10 times for each pre-selected test point. This procedure shall be repeated until all the air discharge completed.

**Indirect discharge for horizontal coupling plane:**

At least 10 single discharges shall be applied to the horizontal coupling plane, at points on each side of the EUT.

Indirect discharge for vertical coupling plane:

At least 10 single discharges shall be applied to the center of one vertical edge of the coupling plane. The coupling plane, of dimensions 0.5m X 0.5m, is placed parallel to, and positioned at a distance of 0.1m from the EUT. Discharges shall be applied to the coupling plane, with this plane in sufficient different positions that the four faces of the EUT are completely illuminated.

TEST MODE

Please refer to the Clause 2.4

TEST RESULTS

Test mode		All			
Type	Type of discharge	Discharge voltage (kV)	Observations Performance	Criteria Level	Result
Direct	Contact discharge	±2	A	B	Pass
		±4	A	B	
	Air discharge	±2	A	B	
		±4	A	B	
		±8	A	B	
Indirect	HCP (6 sides)	±2	A	B	Pass
		±4	A	B	
	VCP (4 sides)	±2	A	B	
		±4	A	B	

Note: The ancillary equipment's specification for an acceptable level of performance or degradation of performance during and/or after the ESD tests.

Description of Discharge Point

Contact discharge-Yellow, Air discharge-Red





4.2. Radio Frequency Electromagnetic Field


PERFORMANCE CRITERION

Standard	Criterion
EN 50024/EN 55035/EN 61000-4-3	Criteria A

TEST LEVEL

Condition of Test	Remark
Fielded strength	3V/m
Radiated signal	Modulated
Scanning frequency	80-1000MHz, 1800MHz, 2600MHz, 3500MHz, 5000MHz
Sweep time of radiated	0.0015 Decade/s
Dwell time	1 Sec.

TEST CONFIGURATION



TEST PROCEDURE

Please refer to EN 61000-4-3 for the measurement methods.

TEST MODE

Please refer to the Clause 2.4

TEST RESULTS

Test mode:	All		
Antenna Polarity	Observations (Performance Criterion)	Criteria Level	Result
H/V	A	A	Pass

4.3. Fast Transients Common Mode

PERFORMANCE CRITERION

Standard	Criterion
EN 50024/EN 55035/EN 61000-4-4	Criteria B

TEST LEVEL


Level: 1KV for AC port, 0.5KV for signal port

Impulse Frequency: 5 kHz;

Tr/Td: 5/50ns;

Burst Duration: 15ms; Burst Period: 300ms

TEST CONFIGURATION



TEST PROCEDURE

Please refer to EN 61000-4-4 for the measurement methods.

TEST MODE

Please refer to the Clause 2.4

TEST RESULTS

Test mode:		All		
Lead under Test	Coupling Direct / Clamp	Observations (Performance Criterion)	Criteria Level	Result
L	Direct	A	B	Pass
N	Direct	A	B	Pass
Signal port	Coupling	A	B	Pass



4.4. Surge

PERFORMANCE CRITERION

Standard	Criterion
EN 50024/EN 55035/EN 61000-4-5	Criteria B

TEST LEVEL


Level: 1kV for line to line, 2kV for line to ground

Voltage Waveform: 1.2/50 us; Current Waveform: 8/20 us

Pulse quantity: 5, interval time: 60 seconds

Phase: 0°, 90°, 180°, 270°

TEST CONFIGURATION



TEST PROCEDURE

Please refer to EN 61000-4-5 for the measurement methods.

TEST MODE

Please refer to the Clause 2.4

TEST RESULTS

Test mode:		All		
Lead under Test	Phase	Observations (Performance Criterion)	Criteria Level	Result
L - N	0°/90°/180°/270°	A	B	Pass
Signal line	/	A	B	Pass

4.5. Radio frequency common mode

PERFORMANCE CRITERION

Standard	Criterion
EN 50024/EN 55035/EN 61000-4-6	Criteria A

TEST LEVEL

Test frequency range: 150 kHz~80MHz

Level: 0.15MHz~10MHz 3V r.m.s

10MHz~30MHz 3V to 1V r.m.s

30MHz~80MHz 1V r.m.s


Modulation type: Amplitude Modulation, 80% depth

Modulated signal: 1 KHz sinusoidal audio signal

Frequency increment step: 1%

Dwell time: 3 seconds

TEST CONFIGURATION



TEST PROCEDURE

Please refer to EN 61000-4-6 for the measurement methods.

TEST MODE

Please refer to the Clause 2.4

TEST RESULTS

Test mode:	All		
Injected Position	Observations (Performance Criterion)	Criteria Level	Result
AC Mains	A	A	Pass
Signal Port	A	A	Pass

4.6. Voltage dips and interruptions

PERFORMANCE CRITERION

Standard	Criterion
EN 50024/EN 55035/EN 61000-4-11	Criteria B for voltage dip Criteria C for voltage interruption

TEST LEVEL


0% of VT (Supply Voltage) for 0.5 period

70% of VT (Supply Voltage) for 25 period

0% of VT (Supply Voltage) for 250 period

Dip quantity: 3, interval time: 10 seconds

TEST CONFIGURATION



TEST PROCEDURE

Please refer to EN 61000-4-11 for the measurement methods.

TEST MODE


Please refer to the Clause 2.4

TEST RESULTS


Test mode:		1, 2			
Test Voltage %	Duration periods	Phase angle	Observations (Performance Criterion)	Criteria Level	Result
0	0.5	0°, 45, 90°, 135°, 180°, 225°, 270°, 315°	A	B	Pass
70	25	0°, 45, 90°, 135°, 180°, 225°, 270°, 315°	A	B	Pass
0	250	0°, 45, 90°, 135°, 180°, 225°, 270°, 315°	C	C	Pass

5. EUT TEST PHOTOS


Conducted Emission (AC Mains)



Conducted Emission (Signal Mains)



Radiated Measurement (30MHz~1000MHz)



Radiated Measurement (1000~6000MHz)




Harmonic Current Emission/ Voltage Fluctuations & Flicker




Electrostatic Discharge



RF electromagnetic field



Injected Current



Electric Fast Transients



Surges



Volt. Interruptions/Volt. Dips




6. PHOTOGRAPHS OF EUT CONSTRUCTIONAL

External Photographs





















Internal Photographs














*****THE END*****