



XonTel MS IP-PBX



General features:

- Support Up to 1000 Extension Numbers.
- Support High Availability and Failover System (Optional).
- Built-in Firewall system for Protection.
- Support Recording system, Incoming and outgoing Calls.
- Full Details and Reports for all Calls.
- Voicemail for Each Number.
- Support Advance Call Center system (Optional).
- Extension on Mobile.
- Can be integrated with many Kinds of databases.
- Support for video-phones.
- Web-based operator panel.
- Call detail record (CDR) report.
- Distributed Dial Plan.
- Conference center with virtual rooms.
- SIP and IAX support.
- Voicemail-to-email functionality.
- Caller ID.
- Multiple trunk support.
- Incoming and outgoing routes with support for dial pattern matching.
- Support for follow-me.
- Support for ring groups.
- Support for paging and intercom.
- Support for time conditions.
- Support for PIN sets.
- DISA (Direct Inward System Access).
- Callback support.
- VoIP provider configuration.
- Support for call queues.
- Dynamically selecting routes by time segment
- Rerouting upon routing failure
- Selecting routes by sequence
- Supports dual security authentication: account password + terminal IP address
- Supports encrypted communication using the TLS or SRTP protocol.
- DND

XonTel MS

Extensions	Up to 1000
Max Concurrent calls	300 concurrent calls
Voicemail	Unlimited
Trunks	Unlimited
IVR	Unlimited
Protocol	SIP, IAX2
Transport protocol	UDP, TCP, TLS
Encryption protocol	SRTP
Codec	G711 a/μ law, G722, OPUS, SILK, G72, G726, G729, GSM, iLBC, H261, H263, H263P, H264, VP8
DTMF	In-band, RFC4733, RFC2833, SIP INFO, Auto
LAN	6 × 10/100Mbps
Firewall	Yes
T.38 Fax	Yes
Power Supply	120V-220V, 88-264VAC
Power Consumption	<10W, 6A
Operating Temperature	-15°C - 60°C
Storage Temperature	-20°C - 80°C
Humidity	0%-95% Relative Humidity, non-condensing
Dimension(W/D/H)	440x216.2x45mm
Weight	5.4kg
Warranty	2 Years