



XT-05

Wi-Fi Security Camera

datasheet

Key Features:

3MP/2K Resolution: Capture high-quality images at 2304x1296 pixels for clear and detailed visuals.

9000mAh Battery: Equipped with a powerful battery that provides long-lasting operation, reducing the need for frequent recharging. It can function for up to 6 months under normal circumstances and standby for 12 months.

110° Viewing Angle

H.265 Video Codec: Utilizes the efficient H.265 video compression algorithm, enabling high-definition video transmission while conserving bandwidth and storage space.

Infrared Night Vision: Equipped with lighting for infrared night vision, with a range of up to 7 meters. Provides clear monitoring throughout the day and night, with IR-CUT switching for accurate color representation during the day and enhanced night vision.

Two-Way Audio with Noise Suppression: Engage in clear and seamless communication using the built-in two-way audio feature, enhanced with noise suppression technology for optimal sound quality.

Wireless Connectivity: Effortlessly connect to your home network using wireless 2.4GHz n/g/b technology, ensuring stable and reliable remote access.

Weatherproof Design: Designed with an IP65 weatherproof rating, suitable for **indoor** use and providing protection against the elements.

Alarm Function: Supports alarm flashing white light and optional night vision red and white light, enhancing security and visibility.

Storage Options: cloud storage, Micro SD card support (up to 128GB), and mobile phone video recording, providing flexible storage options.

2-Year Warranty



| XT-05 | | Specifications |
|-------------------------|-------------------------------|---|
| Master Processor | SOC | Ingenic T31ZL |
| Image Sensor | Sensor | 1/2.8" color CMOS Sensor |
| | Lens | M12, f: 2.8mm, F2.0, 3-megapixel |
| | Visual angle | 110 degrees |
| | Minimum Illumination | 0.01 Lux |
| Audio | Input/Output | Two-way voice intercom available (built-in Microphone and speaker) |
| | Audio Compression Method | AAC |
| Video | Video Compressing Method | H.265 |
| | Lighting Frequency | 50Hz, 60Hz |
| | Image Frame Rate | 15 fps |
| | Maximum Image Resolution | 2304*1296 |
| | Light Source for Night Vision | IR-CUT double optical filter automatic switching, and 8 infrared lights (850nm wavelength) Irradiation distance: 7M |
| Network | Wireless Network | 2.4G Wi-Fi (IEEE802.11b/g/n), built-in antenna |
| | Protocols Supported | TCP/IP, UDP/IP, DHCP, RTMP, MUDP |

| | | |
|---------------------------|---------------------------|--|
| | IP Address Supported | Dynamic IP address supported |
| AI | Intelligent Features | Support Human contour detection, activity zone,intelligent push, pet snapshot |
| Alarm Notification | Alarm Methods | Alarm push by mobile APP, alarm sound |
| Wake-up | Wake-up Method | PIR body induction wake-up, and remote positive wake-up |
| Video Recording | Recording Method | Alarm triggered recording, and manual recording |
| | Video Storage | Cloud storage, local Micro SD card |
| Indicator Lamps | LED Indicator | RGB tri-color lamp indicating the status of power/network signal/functionality |
| Battery | Capacity | 9000mAh |
| | Removability | Unremovable |
| | Battery Life | 6 months (provided that 20 10s videos are recorded per day) |
| | Standby Time | 1 year |
| | Charging Voltage | DV 5V+ -5%/1.5A |
| | Charge Time | Within 8 hours |
| | Protection Method | over-current/over-discharge/over-charge/short circuit/charging protection at high & low temperatures |
| Power Consumption | Standby Power Consumption | 1.68mW(4V 0.42mA) |

| | | |
|----------------------------|---|--|
| | Power Consumption of Daytime Operation | 1W((3.8V 264mA) |
| | Power Consumption of Operation at Night | 2.17W((3.8V 571mA) |
| Interfaces | Power Supply | 1 Type-C Interface |
| | SD Card | 1 Micro SD card (up to 128GB supported) |
| | Keys | 1 on/off button |
| Installation Method | Installation Method | Magnet and 1/4 universal screw holes |
| Environment | Dustproof and waterproof | IP65 |
| | Operating Environment | -10° ~ 45°C /10% ~ 80% (no condensation) |
| | Storage Environment | -20°C ~ 60° /0% ~ 90% (no condensation) |
| Specifications | Size (LxWxH) | 72.1mm×63.3mm×97.4mm (with bracket excluded) |
| | Net Weight of Bare Machine | Approx. 350g |
| | Finished weight | Approx. 570g |
| | Material + Process | ABS |
| | Color | White with high gloss |