



XonTel XT-07P

Wall Mounted IP SIP Phone



The XonTel XT-07P IP Phone is a Hotel phone with succinct design and high cost performance greatly improve work efficiency. Supports 100Mbps of Ethernet, 2 SIP accounts, PoE power supply and other rich functions, compatible with mainstream IP-PBX/soft switch, easy to install and use.

Model	Network	PoE	Power adapter
XT-07P	10/100 Mbps	✓	—

Highlights

- ✓ Exquisite and fashionable product appearance
- ✓ Easy installation and configuration
- ✓ Economical and Environmental friendly product concepts
- ✓ Can store 10 shortcut numbers, long press to achieve speed dial
- ✓ Adaptive 10/100Mbps network port, support POE power supply
- ✓ Compatible with major platforms: Asterisk, Broadsoft, 3CX, Metaswitch, Elastix, Avaya etc.

Generic

- ✓ 2 SIP Lines
- ✓ HD Voice
- ✓ PoE Enabled
- ✓ Handset / Hands-free mode
- ✓ Intelligent DSS Keys
- ✓ Desktop/wall mount mode
- ✓ Optional External Power Supply

Phone Functions

- ✓ Call logs (In/Out/Missed, Max support 600 records in the web)
- ✓ Programmable DSS
- ✓ Action URL / Active URI
- ✓ Web dial

Call Functions

- ✓ Call out / Answer
- ✓ Mute / Unmute
- ✓ Hands-free / Cancel hands-free
- ✓ Call Hold / Resume
- ✓ Speed Dial
- ✓ Redial
- ✓ Auto-Answering
- ✓ 3-way Conference
- ✓ Hot Line
- ✓ Hot desking

Audio

- ✓ Narrowband Codec: G.711a/u, G.726, G.729A, iLBC
- ✓ Wideband Codec: G.722, Opus
- ✓ Acoustic Echo Canceller (AEC)
- ✓ Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR)
- ✓ Packet Loss Concealment (PLC)
- ✓ Dynamic Adaptive Jitter Buffer
- ✓ DTMF: In-band, Out-of-Band – DTMF-Relay(RFC2833) / SIP INFO

Network

- ✓ 10/100 Mbps Ethernet
- ✓ IP Mode:IPv4/IPv6/IPv4&IPv6
- ✓ IP Configuration: Static / DHCP / PPPoE
- ✓ Network Access Control: 802.1x
- ✓ VPN: L2TP / OpenVPN z Web dial
- ✓ VLAN
- ✓ QoS
- ✓ RTCP-XR (RFC3611), VQ-RTCPXR(RFC6035)

Protocols

- ✓ SIP2.0 over UDP/TCP/TLS
- ✓ RTP/RTCP/SRTP
- ✓ STUN
- ✓ DHCP
- ✓ IPv6
- ✓ LLDP
- ✓ PPPoE
- ✓ 802.1x
- ✓ L2TP
- ✓ OpenVPN
- ✓ SNTP
- ✓ FTP/TFTP
- ✓ HTTP/HTTPS
- ✓ TR-069

Deployment & Management

- ✓ Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR-069
- ✓ Web Management Portal
- ✓ Web-based Packet Dump
- ✓ Configuration Export / Import
- ✓ Firmware Upgrade
- ✓ Syslog

Physical Specifications

- ✓ Keypad: 19 keys, including
 - 12 Standard Phone Digits keys (0-9: Speed dial configuration on webpage)
 - 3 Function keys (Hands-free, Redial, Hold)
 - 3 Volume Control keys, Up/Down/Mute (with red color LED)
 - 1 DSS key
- ✓ Status indicator (two-color LED) x1
- ✓ z HD Handset (RJ11) x1
- ✓ z Standard RJ11 Handset Cord x1
- ✓ z RJ11 Port x1
- ✓ z RJ45 Port x1
- ✓ Power: 5V/2A or PoE
- ✓ Power Consumption (PoE): 1.58W~3.47W
- ✓ Power Consumption (Adapter): 0.87~2.23W
- ✓ Working Humidity: 10~90%
- ✓ Installation: Desktop/wall mount
- ✓ Color: Black/white
- ✓ Device Dimensions: 55.8 x 215 x 57.8mm
- ✓ Gift Box Dimensions: 224 x 75 x 62 mm
- ✓ Outer CTN Dimensions: 335 x 323 x 243 mm(20 PCS)
- ✓ Gift Box Dimensions: 224 x 75 x 62 mm
- ✓ Outer CTN Dimensions: 335 x 323 x 243 mm(20 PCS)