



XTM5CAM

5MP IP Dome Camera
(Built-in PoE)

Features:

- Vandal-proof Metal IP Dome Camera
- H.265+ / H.265 / H.264
- 5.0 Mega Pixel
- 4mm F1.6 Lens / 2.8mm F1.6mm
- Built-in PoE
- 15pcs Infrared LEDs
- IR Distance: 10-15 Meters
- Built-in Humanoid Detection
- Onvif Compatible
- Support HTML5 Browser
- P2P and Free Mobile App
- Vandal-proof and Weatherproof for Indoor and Outdoor use




S265



Onvif



Slink



5MP



Motion Detect



APP



D-WDR



Network



Illumination



Human Detect

Specifications:

Camera	
Main Chipset	Ingenico T31X
Sensor	Color 1/2.8" GC4653 CMOS Sensor
Lens	4mm F1.6 Lens / 2.8mm F 1.6 Lens
Min. Illumination	0.02 Lux @ (F1.2, AGC on) 0Lux with IR

Night Vision	15pcs Infrared LEDs
IR Range	15-20Meters
D-WDR	D-WDR (off/low/middle/high)
IR Led Control	Auto/Manual/Off
3D DNR	Off/Low/Middle/High/Higher
Defog	Off/Low/Middle/High
Mirror	Off/ Horizontal Mirror/Vertical Mirror/180-degree flip
Image Setting	Brightness, Contrast, Sharpness, Saturation, Chroma
Humanoid Detection	
Detection Quantity	≤5 people humanoid
Humanoid Size	Humanoid Pixel≥40*40
Detection Ratio	≥99% (meet above requirement)
Capture Corresponding Speed	≤1s
Max Detection Frame	5fps/s
Fault Detection Ratio	≤2%
Detection Part	People with any posture including half body, head, hand, shoulder
Track People	Support
Detection Mode	Support static and dynamic humanoid detection
Detection method	Image detection during day time or night time with lights or IR LEDs
Detection Area	Appointed area, default full-screen
Upload Method	Upload it under private protocol
Trigger Method	Video trigger
Video Encoding	
Video Encode Standard	H.265+(S265)/H.265/H.264
Encoding Feature	Main stream:5MP 2592*1904,4MP 2560*1440@20fps, 3MP 2304*1296@20fps, 2Mp 1920*1080@25fps Sub-stream:D1(720*576),VGA(640*480),Q720P(640*360),CIF(352*288),QVGA(320*240)
Max resolution	5MP (2592*1904)
Video Code Rate	Fixed code rate, variable code rate (Main stream: 160Kbps-4000kbps)
Video Type	Composited stream/video stream
Network Function	
Protocol	TCP/IP, UDP, HTTP, HTTPS, DHCP, RTSP, DDNS, NTP, PPPOE, UPNP, SMTP

Connection Protocol	SLINK ,ONVIF, GB28181 (Option)
Security Mode	Authorized user name and password, HTTPS encryption, AES connecting encryption, RTSP verification
Motion Detection	Set detection area, can set multi-level sensitivity
Privacy Mask Alarm	Support 1 area
Privacy Mask	Support 4 areas
Schedule Linkage	Snapshot, email
Device abnormal Inspection	Support network broken alarm, IP conflict alarm, illegal visiting alarm
Character Overlay (OSD)	Title, time and date overlay, multi-line, and color of characters optional
Port	
Network Port	RJ45 10M/100M network self-adaptation
General	
Operating Temp.	20°C~50°C(-4°F~122°F)
Operating Humidity	Humidity95% or less (non-condensing)
Power Supply	VDC±25%, PoE (IEEE 802.3afClass3)
IP Grade	IP 66
Surge Protection	2KV
Dimensions (mm)	105mm*80mm
Net Weight (kg)	0.35kg