



## XT-M8CAM

4K 8MP IP Bullet Camera

## Features:

- 4K 8MP IP BULLET CAMERA
- S265, H.265/H.264
- 2.7-13.5mm Motorized Lens
- True WDR Function
- Built-in PoE
- 2pcs Large Power Array LEDs
- Built-in Humanoid Detection
- Onvif Compatible
- Support HTML5 Browser
- P2P and Free Mobile App
- Outdoor Weatherproof Metal Case with Bracket




S265



Onvif



Slink



8MP



Motion Detect



APP



WDR



Network



Illumination



Human Detect

## Specification:

Camera	
Chipset	T40XP
Sensor	1/2.8" IMX415 Sony CMOS Sensor
Lens	2.7-13.5mm Motorized 4K Lens
LEDs	2pcs Array LEDs
IR Distance	30-35 meters

D&N	ICR switch, auto/color/B&W/CDS trigger/ customized time
WDR	WDR (Off/Low/Middle/High)
IR Led Control	IR/warm/dual light, auto/manual/off, support 0-100 brightness adjust
3D DNR	Off/Low/Middle/High/Higher
Defog	Off/ON
Mirror	Off/horizontal mirror/vertical mirror/180° flip
Image Setting	Brightness,contrast,sharpness,saturation,chroma
<b>Humanoid Detection</b>	
Detection Quantity	≤10 person
Humanoid Size	Humanoid pixel≥40X40
Detection Ratio	≥99% (meet above requirement)
Capture Corresponding speed	≤1s
Max Detection Frame	5fps/s
Fault Detection Ratio	≤2%
Detect Part	People with any posture including half body,head,hand shoulder
Track People	Support
Detection Mode	Support static and dynamic humanoid detection
Detection Method	Image detection during day or night time with lights or IR Leds
Detection Area	Appointed area, default full-screen
Upload Method	Upload it under private protocol
Trigger Method	Video trigger
<b>Audio &amp; Video Encoding</b>	
Standard	S265,H.265/H.264
Encoding Feature	Main stream:8MP(3840*2160)20fps,5MP(2592*1904)\ 4MP(2560*1440)\3MP(2304*1296)\2MP(1920*1080) 25fps Sub-stream:D1(720*576),VGA(640*480),Q720P(640*360),CIF(352*288),QVGA(320*240)
Max Resolution	8MP 3840*2160
Video Code Rate	Fixed code rate ,variable code rate(main stream:160Kbps-4000kbps)
Video Type	Composited stream/video stream
Audio Standard	G.711u/ G.711A 64Kbps
<b>Network Function</b>	
Network protocol	TCP/IP, UDP, HTTP, HTTPS, DHCP, PPPoE, HTTP, HTTPS, RTSP, RTMP, DDNS, UPNP, FTP
Connection Protocol	Slink, Onvif, GB28181 (option)
Security Mode	Authorized user name and password, HTTPS encryption, AES connecting encryption, RTSP verification
Motion Detection	Set detection area, can set multi-level sensitivity
Occlusion Alarm	Support 1 area
Privacy Mask	Support 4 areas
Schedule Linkage	Snapshot, email
Device Abnormal Inspection	Support network broken alarm, IP conflict alarm, illegal visiting alarm
Character Overlay (OSD)	Title, time and date overlay, multi-line, and color of characters optional

Port	
Network Port	RJ45 10M/100M network self-adaptation
General	
Power Supply	DC12V /PoE
Working Temperature	-20°C ~ + 60°C
Working Humidity	0% ~90 %
IP Grade	IP 66
Size	280mm* 88mm*78mm
Weight	0.88KG